



# Multiple View Geometry: Exercise Sheet 5

Prof. Dr. Daniel Cremers, Julia Diebold, Robert Maier, TU Munich

<http://vision.in.tum.de/teaching/ss2015/mvg2015>

Exercise: June 9th, 2015

---

---

## Part II: Practical Exercises

This exercise is to be solved **during the tutorial**.

### Harris Corner Detector

In this exercise you will implement the Harris corner detector. *Hint: Again, it is possible to implement this exercise without loops. However, we recommend to start with a loop-based version, and only afterwards replace the loops by single function calls. For quick testing, we provide a small image `small.png`*

1. Download `ex5.zip` from the website.
2. Compute the structure tensor as introduced in the lecture for every pixel of `img1`. As weighting function use a Gaussian Kernel with a standard deviation of  $\sigma_w = 3$  pixel, and an integration window size of  $2\sigma_w + 1$  pixel. *Hint: use `normpdf` and `conv2`.*

The structure tensor  $M$  for pixel  $x, y$  is a  $2 \times 2$  matrix, which summarizes the structure of the image in the vicinity (determined by  $\sigma_w$ ) of the pixel  $x, y$ . It can e.g. be interpreted as (weighted) covariance matrix of the image gradient around the pixel, and is computed as

$$M(x, y) := \sum_{(x', y')} w(x' - x, y' - y) \begin{pmatrix} I_x^2(x', y') & I_x(x', y')I_y(x', y') \\ I_x(x', y')I_y(x', y') & I_y^2(x', y') \end{pmatrix} \quad (1)$$

where  $I_x$  and  $I_y$  are the  $x$  and  $y$  image gradient computed using central differences, and  $w$  is the weighting function, here a zero-mean two-dimensional Gaussian with covariance  $\sigma_w^2 I_{2 \times 2}$ .

3. Compute the scoring function  $C(x, y) := \det(M(x, y)) + \kappa \text{trace}^2(M(x, y))$  using  $\kappa = 0.05$ . Visualize the scoring function using `imagesc`. *Hint: if you cannot see much, try to display a non-linearly transformed scoring function, e.g.  $\text{sign}(C) \cdot |C|^{\frac{1}{4}}$ .*
4. Find all pixels  $x$  for which  $C(x) > \theta$ , and which are a local maximum of the scoring function, i.e., all four adjacent pixel have a lower score (non-maximum suppression). Use  $\theta = 10^{-7}$ . Display the found Harris Corners using the provided function `drawPts`.
5. Try different values for  $\sigma_w$  - what do you observe?

### Patch Tracking

1. Compute the local velocity of each pixel from `img1` to `img2`, using the formula from the slides. You can re-use the computed structure tensor from the first exercise. Visualize your result using `imagesc` *Hint: Implementing this exercise without loop is somewhat tricky.*
2. *Optional: Implement Lucas-Kanade Patch-Tracking, by iteratively re-computing the estimated velocity at the new position. Use it to track the Harris Corners found in exercise 1.*