# Chapter 10 Variational Multiview Reconstruction

Multiple View Geometry Summer 2016 Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Variational Multiview Reconstruction

Super-resolution Texture Reconstruction

Space-Time Reconstruction from Multiview Video

Prof. Daniel Cremers
Chair for Computer Vision and Pattern Recognition
Department of Computer Science
Technische Universität München



- 1 Shape Representation and Optimization
- 2 Variational Multiview Reconstruction
- **3** Super-resolution Texture Reconstruction

4 Space-Time Reconstruction from Multiview Video

Shape Representation and Optimization

Variational Multiview
Reconstruction
Super-resolution
Texture Reconstruction

#### **Shape Optimization**

Shape optimization is a field of mathematics that is focused on formulating the estimation of geometric structures by means of optimization methods.

Among the major challenges in this context is the question how to mathematically represent shape. The choice of representation entails a number of consequences, in particular regarding the question of how efficiently one can store geometric structures and how efficiently one can compute optimal geometry.

There exist numerous representations of shape which can loosely be grouped into two classes:

- Explicit representations: The points of a surface are represented explicitly (directly), either as a set of points, a polyhedron or a parameterized surface.
- Implicit representations: The surface is represented implicity by specifying the parts of ambient space that are inside and outside a given surface.

Variational Multiview

Prof. Daniel Cremers



Shape Representation and Optimization

Variational Multiview Reconstruction


Super-resolution Texture Reconstruction

## **Explicit Shape Representations**


An explicit representations of a closed curve  $C \subset \mathbb{R}^d$  is a mapping  $C : \mathbb{S}^1 \to \mathbb{R}^d$  from the circle  $\mathbb{S}^1$  to  $\mathbb{R}^d$ . Examples are polygons or – more generally – spline curves:

$$C(s) = \sum_{i=1}^{N} C_i B_i(s),$$

where  $C_1, \ldots, C_N \in \mathbb{R}^d$  denote control points and  $B_1, \ldots, B_N : \mathbb{S}^1 \to \mathbb{R}$  denote a set of spline basis functions:



basis functions



spline & control points

Variational Multiview
Reconstruction

Prof. Daniel Cremers



Shape Representation and Optimization

Variational Multiview Reconstruction


Super-resolution Texture Reconstruction

#### **Explicit Shape Representations**

Splines can be extended from curves to surfaces or higher dimensional structures. A spline surface  $S \subset \mathbb{R}^d$  can be defined as:

$$S(s,t) = \sum_{i,j} C_{i,j} B_i(s) B_j(t),$$

where  $C_{i,j} \in \mathbb{R}^d$  denote control points and  $B_1, \ldots, B_N : [0,1] \to \mathbb{R}$  denote a set of spline basis functions. Depending on whether the surface is closed or open these basis functions will have a cyclic nature (as below) or not:



C<sub>1,0</sub> C<sub>1,2</sub> C<sub>2,2</sub> C<sub>0,2</sub> C<sub>0,2</sub>

spline surface & cntrl. points

Variational Multiview Reconstruction

Prof. Daniel Cremers



Shape Representation and Optimization

Variational Multiview Reconstruction Super-resolution

Texture Reconstruction
Space-Time

Reconstruction from Multiview Video

## **Implicit Shape Representations**

One example of an implicit representation is the indicator function of the surface S, which is a function  $u:V\to\{0,1\}$  defined on the surrounding volume  $V\subset\mathbb{R}^3$  that takes on the values 1 inside the surface and 0 outside the surface:

$$u(x) = \begin{cases} 1, & \text{if } x \in \text{int}(S) \\ 0, & \text{if } x \in \text{ext}(S) \end{cases}$$

Another example is the signed distance function  $\phi:V\to\mathbb{R}$  which assigns all points in the surrounding volume the (signed) distance from the surface S:

$$\phi(x) = \begin{cases} +d(x,S), & \text{if } x \in \text{int}(S) \\ -d(x,S), & \text{if } x \in \text{ext}(S) \end{cases}$$

Depending on the application it may be useful to know for every voxel how far it is from the surface. Signed distance functions can be computed in polynomial time. MatLab: bwdist.

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Variational Multiview Reconstruction Super-resolution

Texture Reconstruction
Space-Time

Reconstruction from Multiview Video

## **Explicit Versus Implicit Representations**

In general, compared to explicit rerpresentations the implicit representations have the following strengths and weaknesses:

- Implicit representations typically require more memory in order to represent a geometric structure at a specific resolution. Rather than storing a few points along the curve or surface, one needs to store an occupancy value for each volume element.
- Moving or updating an implicit representation is typically slower: rather than move a few control points, one needs to update the occupancy of all volume elements.
- + Methods based on implicit representations do not depend on a choice of parameterization.
- + Implicit representations allow to represent objects of arbitrary topology (i.e. the number of holes is arbitrary).
- With respect to an implicit representation many shape optimization challenges can be formulated as convex optimization problems and can then be optimized globally.

Variational Multiview Reconstruction

Prof. Daniel Cremers



Shape Representation

Variational Multiview Reconstruction

Super-resolution
Texture Reconstruction

## **Multiview Reconstruction as Shape Optimization**

How can we cast multiple view reconstruction as a shape optimization problem? To this end, we will assume that the camera orientations are given.

Rather than estimate the correspondence between all pairs of pixels in either image we will simply ask:

How likely is a given voxel x on the object surface S?

If the voxel  $x \in V$  of the given volume  $V \subset \mathbb{R}^3$  was on the surface then (up to visibility issues) the projection of that voxel into each image should give rise to the same color (or local texture). Thus we can assign to each voxel  $x \in V$  a so-called photoconsistency function

$$\rho: V \to [0,1],$$

which takes on low values (near 0) if the projected voxels give rise to the same color (or local texture) and high values (near 1) otherwise.

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

ariational Multiview leconstruction

Super-resolution Texture Reconstruction

# **A Weighted Minimal Surface Approach**

The reconstruction from multiple views can now be formulated as finding the maximally photoconsistent surface, i.e. a surface  $S_{opt}$  with an overall minimal photoconsistency score:

$$S_{opt} = \arg\min_{S} \int_{S} \rho(s) ds.$$
 (1)

This seminal formulation was proposed among others by Faugeras & Keriven (1998). Many good reconstructions were computed by starting from an initial guess of *S* and locally minimizing this energy using gradient descent. But can we compute the global minimum?

The above energy has a central drawback:

The global minimizer of (1) is the empty set.

It has zero cost while all surfaces have a non-negative energy. This short-coming of minimal surface formulations is often called the shrinking bias. How can we prevent the empty set?

Variational Multiview
Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

econstruction

Texture Reconstruction
Space-Time
Reconstruction from
Multiview Video

Super-resolution

# **Imposing Silhouette Consistency**

Assume that we additionally have the silhouette  $S_i$  of the observed 3D object outlined in every image  $i=1,\ldots,n$ . Then we can formulate the reconstruction problem as a constrained optimization problem (Cremers, Kolev, PAMI 2011):

$$\min_{\mathcal{S}} \int_{\mathcal{S}} \rho(s) ds$$
, such that  $\pi_i(\mathcal{S}) = \mathcal{S}_i \ \forall i = 1, \dots, n$ .

Written in the indicator function  $u: V \to \{0, 1\}$  of the surface S this reads:

$$\min_{u:V\to\{0,1\}} \int_{V} \rho(x) |\nabla u(x)| dx$$
s. t. 
$$\int_{R_{ij}} u(x) dR_{ij} \geq 1, \text{ if } j \in S_{i} \qquad (*)$$

$$\int_{R_{ij}} u(x) dR_{ij} = 0, \text{ if } j \notin S_{i},$$

where  $R_{ij}$  denotes the visual ray through pixel j of image i.

Variational Multiview

Prof. Daniel Cremers




Shape Representation and Optimization

riational Multiview

Super-resolution Texture Reconstruction

## **Imposing Silhoutte Consistency**



Top view of the geometry and respective visual rays.

Any ray passing through the silhoutte must intersect the object in at least one voxel.

Any ray passing outside the silhouette may not intersect the object in any pixel.

Cremers, Kolev, PAMI 2011

Variational Multiview Reconstruction

Prof. Daniel Cremers



Shape Representation and Optimization

Reconstruction

Super-resolution Texture Reconstruction

## **Convex Relaxation and Thresholding**

By relaxing the binarity constraint on u and allowing intermediate values between 0 and 1 for the function u, the optimization problem (\*) becomes convex.

#### **Proposition**

The set

$$\mathcal{D} := \left\{ u: V \to [0,1] \left| \begin{array}{c} \int_{R_{ij}} u(x) \ dR_{ij} \geq 1 & \text{if } j \in S_i \ \forall i,j \\ \int_{R_{ij}} u(x) \ dR_{ij} = 0 & \text{if } j \notin S_i \ \forall i,j \end{array} \right\} \right.$$

of silhouette consistent functions is convex.

#### Proof.

For a proof we refer to Kolev, Cremers, ECCV 2008.

Thus we can compute solutions to the silhouette constrained reconstruction problem by solving the relaxed convex problem and subsequently thresholding the computed solution.

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

ariational Multiview

Super-resolution Texture Reconstruction

# **Reconstructing Complex Geometry**

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Super-resolution Texture Reconstruction







3 out of 33 input images of resolution  $1024 \times 768$ Data courtesy of Y. Furukawa.

# **Reconstructing Complex Geometry**

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 




Shape Representation and Optimization

ariational Multiview

Super-resolution Texture Reconstruction

Space-Time Reconstruction from Multiview Video



Estimated multiview reconstruction

Cremers, Kolev, PAMI 2011

#### **Reconstruction from a Handheld Camera**

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

riational Multivie

Super-resolution Texture Reconstruction

Space-Time Reconstruction from Multiview Video



2/28 images

Estimated multiview reconstruction


Cremers, Kolev, PAMI 2011

#### **Multi-view Texture Reconstruction**

In addition to the dense geometry S, we can also recover the texture  $T: S \to \mathbb{R}^3$  of the object from the images  $\mathcal{I}_i: \Omega_i \to \mathbb{R}^3$ . Rather than simply back-projecting respective images onto the surface, Goldlücke & Cremers ICCV 2009 suggest to solve a variational super-resolution approach of the form:

$$\min_{T:S\to\mathbb{R}^3}\sum_{i=1}^n\int\limits_{\Omega_i}\left(b*\left(T\circ\pi_i^{-1}\right)-\mathcal{I}_i\right)^2dx\,+\,\lambda\int\limits_{S}\|\nabla_{\!\!_S}\,T\|ds,$$

where b is a linear operator representing blurring and downsampling and  $\pi_i$  denotes the projection onto image  $\Omega_i$ :



Variational Multiview
Reconstruction

Prof. Daniel Cremers



Shape Representation and Optimization

Variational Multiview

Reconstruction
Super-resolution

#### **Multi-view Texture Reconstruction**

The super-resolution texture estimation is a convex optimization problem which can be solved efficiently. It generates a textured model of the object which cannot be distinguished from the original:



One of 36 input images



textured 3D model

Goldlücke, Cremers, ICCV 2009, DAGM 2009

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Variational Multiview Reconstruction

#### **Multi-view Texture Reconstruction**

The super-resolution approach exploits the fact that every surface patch is observed in multiple images. It allows to invert the blurring and downsampling, providing a high-resolution texturing which is sharper than the individual input images:





input image close-up

super-resolution texture

Goldlücke, Cremers, ICCV 2009, DAGM 2009

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Variational Multiview Reconstruction

Texture Reconstruction
Space-Time

Reconstruction from Multiview Video

#### Space-Time Reconstruction from Multi-view Video

Although laser-based reconstruction is often more accurate and more reliable (in the absence of texture), image-based reconstruction has two advantages:

- One can extract geometry and color of the objects.
- On can reconstruct actions over time filmed with multiple synchronized cameras.

Oswald & Cremers 4DMOD 2013 and Oswald, Stühmer, Cremers, ECCV 2014, propose convex variational approaches for dense space-time reconstruction from multi-view video.













1/16 input videos

Dense reconstructions over time

Oswald, Stühmer, Cremers, ECCV 2014

Variational Multiview Reconstruction

**Prof. Daniel Cremers** 



Shape Representation and Optimization

Variational Multiview Reconstruction

Super-resolution Texture Reconstruction

pace-Time econstruction from

#### **Toward Free-Viewpoint Television**

Space-time action reconstructions as done in Oswald & Cremers 2013 entail many fascinating applications, including:

- For video conferencing one can transmit a full 3D model of a speaker which gives stronger sense of presence and immersion.
- For sports analysis one can analyze the precise motion of a gymnast.
- For free viewpoint television, the spectator at home can interactively chose from which viewpoint to follow an action.







Textured action reconstruction for free-viewpoint television

Oswald, Cremers, 4DMOD 2013

Variational Multiview Reconstruction

Prof. Daniel Cremers



Shape Representation and Optimization

Variational Multiview Reconstruction

Super-resolution Texture Reconstruction